



PRODUCT DATA SHEET

Premium Quality Lubricants

NATIONAL™ SYNTHETIC MULTIVEHICLE ATF SYNTHETIC MULTIVEHICLE AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION

NATIONAL™ Synthetic Multivehicle ATF is specially formulated using synthetic base stocks, seal conditioner and other performance additives to exceed the performance and protection requirements of newer and rebuilt transmissions. Installers can rely on this single fluid to conveniently and accurately meet a wide array of global OEM requirements in North America.

INDUSTRY AND OEM SPECIFICATIONS

- Exceeds performance requirements of Dexron III H/ Mercon fluid
- Suitable for use in Ford Mercon V* applications
- Suitable for use in Nissan & Infiniti Matick D/J/K applications
- Suitable for use in Chrysler transmissions requiring ATF +3, ATF+4* applications
- Meets performance requirements of Toyota and Lexus JWS 3309/Type T III & IV applications
- Suitable for use in Land Rover Texaco N402 applications
- Suitable for use in Jaguar Idemitsu K17 applications
- Exceeds performance requirements of JASO M315-2004
- Suitable for use in Honda and Acura ATF-Z1 applications
- Suitable for use in Hyundai/KIA SP II/ SPIII applications
- Suitable for use in Mazda ATF M-III, ATF M-V
- Suitable for use in Allison C-4, TES 295* and TES-389 applications
- Suitable for use in Audi/VW Part#G 052 025 (09M), G 052 990 (09A) applications
- Suitable for use in Mercedes-Benz, page 236.9/10/11; ATF 3403 M-115 applications
- Exceeds performance requirements of MAN 339 V1; 339 Z2
- Suitable for use in Volvo Part#1161540-8 applications
- Exceeds performance requirements of Voith H55.6335 (G607)
- Suitable for ZF TE-ML 03D/04D/09/14A/14B/16L,17C applications

* Viscosity requirement is not met

**** Not recommended for CVT applications**

TYPICAL PROPERTIES

Viscosity @100°C	D445	7.5
Viscosity Index	D2770	150
Pour Point °C	D97	-40
Color	Visual	Red

Rev: 03/10/11